APPENDIX T

TRAILER INSPECTION CHECKLIST

This appendix contains a trailer inspection checklist that provides both general guidelines and a procedure for inspecting trailers. Items to be inspected are categorized under major systems. For data about a particular type of trailer, see the TM for that trailer.

INSPECTION CRITERIA

• Trailer Body.
☐ Trailer body is securely mounted on frame; all mounting bolts are present and properly secured.
■ Metal bodies.
 ☐ Metal bodies are free of dents, cracks, and rusty areas; there is no warping. ☐ Tailgate is securely mounted; it operates freely and fits tailgate opening properly. Tailgate fasteners and chains are in place and serviceable. ☐ Vehicle bodies are kept drained to prevent rust.
■ Wood bodies.
 ☐ Flooring is not cracked, broken, or excessively worn; there is no warping. ☐ Sideboards are in place and in good condition. ☐ Tailgates are properly mounted.
• Tarpaulins and Bows.
 ☐ Bows and racks are smooth and free of splinters. ☐ Bows and racks are serviceable and securely mounted.
NOTE: Bolts in racks and bows should be installed with bolt heads out to prevent damage to canvas.
☐ All tarps and end curtains are on hand and in serviceable condition. ☐ Canvas is mounted correctly (not inside out). ☐ Ropes or straps are not frayed, broken, or missing. Tie-down strap hooks are not bent, broken, or missing.

• Trailer Chassis.

	 □ Trailer chassis has no cracks, breaks, or broken welds. □ Frame is not sprung. □ The lunette or kingpin is properly mounted, secured, clean, and lubricated. □ Data plates and decals (when used) are secure, clean, and legible. □ Chock blocks are in place and properly secured. □ Landing legs are not bent; they operate freely. 	
• Tires.		
	 □ Tires have proper inflation. □ Tread is sufficient; there are no cuts, bruises, or breaks. □ There is no evidence of unusual wear. □ There are no rocks between duals. □ Valve caps are in place; valve stems are serviceable. □ Spare tire is in place and serviceable. 	
• Electrical System and Reflectors.		
	 □ All lights are mounted securely and in operating condition. □ Wires are not worn or frayed. □ Lenses are not cracked or discolored. □ Plug receptacle has cap and gasket; spring lid fits properly. □ Plug receptacle contacts are serviceable and free of dirt and corrosion. □ All reflectors are in place; lenses are not cracked, missing, or painted over. 	
Brake System.		
freely.	 □ Air coupling seal is serviceable; dummy coupling, with chain, is present. □ Coupling should attach easily; there is no air leak when attached. □ Air cylinder on trailer (when applicable) is securely mounted and operates 	
	 □ Cylinder boot is not torn or loose in mounting. □ Air lines are free of water (air filter is clean). □ The master cylinder reservoir has proper fluid level (see appropriate TM for 	
specifications).	☐ Hand brake is adjusted and operates properly.	